

Van Loading Ramps



Fig 43▲ Solid Ramp with gate facility allowing ramp to fully swing out so that van can be loaded manually if necessary and to its full capacity.

| Solid Gate Ramp | Length | Stowed Height | Overall Width | SWL |
|-----------------|---------------|---------------|---------------|---------------|
| FVRSG1 | 90.5"/2300mm | 49.2"/1250mm | 31.5/800mm | 400/500/750kg |
| FVRSG2 | 110.2"/2800mm | 59"/1500mm | 31.5/800mm | 400/500/750kg |
| FVRSG3 | 120"/3000mm | 63"/1600mm | 31.5/800mm | 400/500/750kg |

Solid Ramp offered in 3 standard sizes to suit most types of commercial vehicles.

| Solid Ramp | Length | Stowed Height | Overall Width | SWL |
|------------|---------------|---------------|---------------|---------------|
| FVRS1 | 90.5"/2300mm | 49.2"/1250mm | 31.5/800mm | 400/500/750kg |
| FVRS2 | 110.2"/2800mm | 59"/1500mm | 31.5/800mm | 400/500/750kg |
| FVRS3 | 120"/3000mm | 63"/1600mm | 31.5/800mm | 400/500/750kg |

Fixed Van Ramps are available in all combinations and sizes to suit customer needs.